

WE CLAIM:

- 102
Larkin
SEP
Fig. 4
1. A flying insect trap, using insect attractant light displayed onto a substantially planar mounting surface, said trap comprising:
- (a) means for mounting the flying insect trap on the planar mounting surface;
 - (b) at least one source of insect attractant light;
 - (c) at least one insect immobilization surface; and
 - (d) a housing, the housing configured to cooperate with the source of insect attractant light such that light from the source is directed into at least three insect attracting light patterns formed on the planar mounting surface.

2. The trap of claim 1 wherein the housing comprises three sides and one of each of the three patterns is formed on one of each of the three sides of the housing.

3. The trap of claim 1 wherein each light pattern comprises radiated light.

4. The trap of claim 1 wherein each light pattern comprises both reflected and radiated light.

5. The trap of claim 1 wherein the three insect attracting light patterns are separated by about 120 degrees.

- 103
Larkin
6. The trap of claim 1 wherein the housing is configured to cooperate with the source of insect attractant light such that light from the source is directed into four insect attracting light patterns formed on the planar mounting surface.

- 103
Larkin
7. The trap of claim 6 wherein the four insect attracting light patterns are separated by about 90 degrees.

103 8. The trap of claim 1 wherein the source of insect attractant light comprises at least one source of ultraviolet light.

102 9. The trap of claim 1 wherein the insect immobilization surface comprises an adhesive surface.

103
Larkin 10. The trap of claim 9 wherein the adhesive surface is mounted on the planar mounting surface.

102
Larkin 11. The trap of claim 9 wherein the adhesive surface is mounted on a portion of the housing.

102
Larkin 12. The trap of claim 1 wherein the planar mounting surface comprises a wall surface.

102
Larkin 13. The trap of claim 1 wherein the planar mounting surface comprises a ceiling surface.

102
Larkin 14. The trap of claim 1 wherein the housing comprises at least one internal reflecting surface positioned such that light from the source is directed onto the planar mounting surface.

102
Larkin 15. The trap of claim 14 wherein the reflecting surface is a planar reflecting surface.

103
Larkin 16. The trap of claim 14 wherein the reflecting surface is a curved reflecting surface.

102
Larkin 17. The trap of claim 1 wherein the trap further comprises an insect attractant composition.

103
Larkin 18. The trap of claim 1 wherein the housing comprises a one piece housing surrounding the source of insect attractant light.

103
Larkin 19. The trap of claim 18 wherein the housing comprises an open rectangular parallelepiped, said open, rectangular parallelepiped having two parallel surfaces comprising openings for the insect attractant light.

102
Larkin 20. The trap of claim 1 wherein the housing comprises three openings.

103
Larkin 21. The trap of claim 1 wherein the housing comprises four openings.

102 Larkin 22. The trap of claim 1 wherein the light patterns are non-overlapping.

102
Larkin 23. The trap of claim 1 wherein the trap shape is a regular geometric pattern.

103
Larkin 24. The trap of claim 1 further including three light sources, each light source creating a separate light pattern.

103 25. The trap of claim 24 wherein at least one of the three light sources is an ultraviolet bulb.

103 26. The trap of claim 24 wherein the three light sources are ultraviolet bulbs having a tubular configuration.

103
Larkin 27. The trap of claim 1 wherein the housing includes a triangular planar plate.

28 A flying insect trap, using insect attractant light displayed onto a substantially planar mounting surface, said trap comprising:

(a) means for mounting the flying insect trap on the mounting surface;

- (b) at least three sources of insect attractant light, including:
- (i) a first source;
 - (ii) a second source; and
 - (iii) a third source;
- (c) at least one insect immobilization surface;
- (d) a housing having a triangular configuration, the housing comprising at least three side openings, including:
- (i) a first side opening located on a first side of the housing;
 - (ii) a second side opening located on a second side of the housing;
 - (iii) a third side opening located on a third side of the housing; and
- (e) the first, second, and third side openings configured to partially enclose the first, second, and third sources of insect attractant light and cooperate with the sources of insect attractant light such that light from the sources is directed onto the planar mounting surface to form at least three non-overlapping insect attracting light patterns, including:
- (i) a first light pattern;
 - (ii) a second light pattern spaced 120 degrees from the first light pattern; and
 - (iii) a third light pattern spaced 120 degrees from the second light pattern.

add 120